


> Standard Filter Driers
> Déshydrateurs standards

> Standard Filter-Trockner
> Filtri disidratatori standar

> Deshidratadores standard


O-Ring



197 mm
Ø 76 mm
In 5/8"-18UNF Male
Out 5/8"-18UNF Female
Switch port: Female

33363


O-Ring



In Out 200 mm
Ø 60 mm
In Nr.4 Male
Out Nr.4 Male
Switch port:

330000


O-Ring



In Out 150 mm
Ø 60 mm
In 5/8"-18UNF Male
Out 5/8"-18UNF Male
Switch port: Female

3300001


O-Ring



In Out 191 mm
Ø 60 mm
In 5/8"-18UNF Male
Out 5/8"-18UNF Male
Switch port: Female

33232

O-Ring



In Out 225 mm
Ø 63 mm
In 5/8"-18UNF Male
Out 5/8"-18UNF Male
Switch port: Female

33926


O-Ring



In Out 203 mm
Ø 70 mm
In 20mm Male
Out 16mm Male
Switch port: Female

3300011


O-Ring



In Out 200 mm
Ø 76 mm
In 5/8"-18UNF Male
Out 5/8"-18UNF Male
Switch port: Female

33803


O-Ring



In Out 210 mm
Ø 63 mm
In 5/8"-18UNF Male
Out 5/8"-18UNF Female
Switch port: Female

3300003

O-Ring



In Out 150 mm
Ø 75 mm
In 5/8"-18UNF Male
Out 5/8"-18UNF Male
Switch port: Female

33282


O-Ring



In Out 203 mm
Ø 76 mm
In 5/8"-18UNF Female
Out 5/8"-18UNF Female
Switch port:

33215


O-Ring



In Out 198 mm
Ø 60 mm
In 5/8"-18UNF Male
Out 5/8"-18UNF Female
Switch port:

33255


Flare



In Out 215 mm
Ø 63 mm
In 5/8"-18UNF Male
Out 5/8"-18UNF Male
Switch port: Fem. + male

33258


O-Ring



222 mm
Ø 76 mm
In 5/8"-18UNF Male
Out 5/8"-18UNF Male
Switch port: Female + Press. Relief valve

33264


O-Ring



228 mm
Ø 76 mm
In 5/8"-18UNF Male
Out 5/8"-18UNF Male
Switch port: Fuse plug

33307


O-Ring



203 mm
Ø 63 mm
In 5/8"-18UNF Male
Out 5/8"-18UNF Male
Switch port: Female

33321


O-Ring



192 mm
Ø 63 mm
In 5/8"-18UNF Male
Out 5/8"-18UNF Male
Switch port: Fem.+male

33455


O-Ring



213 mm
Ø 63 mm
In 5/8"-18UNF Male
Out 5/8"-18UNF Female
Switch port: Fem. + Male

3300014


O-Ring



213 mm
Ø 63 mm
In 5/8"-18UNF Male
Out 5/8"-18UNF Male
Switch port: Fem. + R134a

3300013

O-Ring



200 mm
Ø 76 mm
In 20 mm Male
Out 16 mm Male
Switch port: Female

33424

O-Ring



215 mm
Ø 88 mm
In 3/4" Male
Out 3/4" Female

33705

> Standard Filter Driers
> Déshydrateurs standards

> Standard Filter-Trockner
> Filtri disidratatori standar

> Deshidratadores standard

3


Bracket



60 mm
2-1/2"

160029


Bracket



75 mm
3"

160030


O-Ring Diavia 017047



223 mm
63 mm
In 5/8"-18UNF Male
Out 5/8"-18UNF Female
Switch port: Male

33808


O-Ring Diavia 017040



210 mm
63 mm
In 9/16"-18UNF Male
Out 9/16"-18UNF Male
Switch port: Male

330006


O-Ring Diavia 017016



181 mm
76 mm
In 5/8"-18UNF Male
Out 5/8"-18UNF Male
Switch port:

330007


O-Ring Diavia 017045



228 mm
50 mm
In 5/8"-18UNF Male
Out 5/8"-18UNF Male
Switch port: Male

330008


O-Ring Diavia 017048



173 mm
76 mm
In 5/8"-18UNF Male
Out 5/8"-18UNF Female
Switch port:

330009


O-Ring Diavia 017050



230 mm
76 mm
In 5/8"-18UNF Male
Out 5/8"-18UNF Male
Switch port: Male

33834


O-Ring Diavia 017046



210 mm
64 mm
In 5/8"-18UNF Male
Out 5/8"-18UNF Female
Switch port: Male

330012


Flare Bus Applications



180 mm
76 mm
In 1/2" SAE Male
Out 1/2" SAE Male
Capacity 225 CC DCY 164

330020


Flare Bus Applications



185 mm
76 mm
In 5/8"-18UNF Male
Out 5/8"-18UNF Male
Capacity 225 CC DCY 185

330021


Flare Bus Applications



240 mm
76 mm
In 1/2" SAE Male
Out 1/2" SAE Male
Capacity 480 CC DCY 304

330022

Flare Bus Applications



245 mm
76 mm
In 5/8"-18UNF Male
Out 5/8"-18UNF Male
Capacity 480 CC DCY 305

330023

Flare Bus Applications

Flare Bus Applications

Flare Bus Applications